International Journal of Engineering Research and General Science Volume 2, Issue 2, Feb-Mar 2014 ISSN 2091-2730

Effect of Velocity and Particle Size on the Coefficient of Heat Transfer in

Fluidized Bed Heat Exchanger

Anusaya M. salwe¹, Shubham S.Pande¹, Juned S.Khan¹

¹Scholar, Manoharbhai Patel Institute of Engineering and Technology, Shahapur, Bhandara, R.T.M. Nagpur University, Nagpur

Pandeshubham030@gmail.com

ABSTRACT - Fluidized bed Heat exchangers are important inmany industrial applications. Understanding how a fluidized bed as a multiphase flow system operates will improve its capabilities and operations. Minimum fluidization velocity and local gas holdup are important parameters used to characterize the hydrodynamic behavior of a material inside the fluidized bed.

Fluidization is the phenomenon of imparting the properties of a fluid to a bed of particulate solids by passing atmospheric air through the material. Fluidized beds are reactors in which fluidization of particulate solids takes place. Fluidized beds are an important asset in many industrial processes because they present several advantages that include a high rate of heat and mass transfer, low pressure drops, and uniform temperature distribution.

Experiments have been carried out in a setup i.e. in a fluidized bed heat exchanger, to find out the Heat transfer coefficient between different silica sand particles and in different velocities of air. The whole sand bed is heated by cartage heater. An experiment is performed with three different sand particles with different diameter and ten different gas velocities. The bed particles are chosen by taking Geldart's criteria. Silica sand particles are of diameter 300-450µm, 425-650µm and 600-850µm. Fluidization is carried out by using air having normal temperature.

It was found in literature survey that Higher rate of heat transfer is obtained by increasing the flow rate and by decreasing the size of the particle.

The experimental results showed that the Heat transfer coefficient is increased with increasing the air velocity. It is also found that the Heat transfer decrease by increasing the particle size for Geldart B group particles.

Keywords: Fluidization, Fluidized bed heat exchanger, Bubbling Fluidization, Silica sand, heat transfer, Thermal coefficient, Heat Transfer coefficient, Operating variables, Gas velocity

1. INTRODUCTION

The major objectives of this work are to study the heat transfer effect on the fluidized bed, to determining the heat transfer rate at different points in the fluidized bed, to determine the effect of heat transfer at different sand particle and with varying velocity of air. A setup of thermal-coil is inserted in the fluidized bed to study the effect of heat transfer rate from the particle to fluid that is air bubbling Gas-Solid fluidized bed in order to find the suitability of sand as a bed material in Gas-Solid fluidized bed An experiment has been carried out in a setup of fluidized bed heat exchanger with atmospheric air as a fluidizing medium and silica sand of diameter 300-450 µm, 425-650 µm and 600-850 µm diameter.

When a gas flow is introduced through the bottom of a bed of solid particles, it moved upward through the bed via the empty spaces between the particles. At low gas velocities, aerodynamic drag on each particle has also low, and thus the bed remained in a fixed state. Increased in the velocity, the aerodynamic drag forces started to counteract the gravitational forces caused the bed to expand in volume as the particles moved away from each other. Further increasing the velocity, it is reached a critical value at which the upward drag forces exactly equal the downward gravitational forces, caused the particles to become suspended within the fluid. At this critical value, the bed is said to be fluidized and is exhibit fluidic behavior. By further increased in gas velocity, the bulk density of the bed is decreased, and its fluidization became more efficient, until the particles no longer formed a bed and are "conveyed" upwards by the gas flow. When it fluidized, a bed of solid particles behaved as a fluid, like a liquid or gas.

A large amount of research is done on this technology due to the advantages of fluidized bed reactors. Most current research have been done to explain how the velocity of gas affects the heat transfer in fluidized bed under varying particle size and velocity of air. Lots of literature available on the heat transfer coefficient, but there is considerably less literature available on the heat transfer coefficient in that they give effect of different velocities on heat transfer in presence of horizontal cartage heater.

www.ijergs.org

International Journal of Engineering Research and General Science Volume 2, Issue 2, Feb-Mar 2014 ISSN 2091-2730



Figure1: schematic drawing of a fluidized bed

Anusaya M. Salwe, 2013 made her study on Local heat transfer coefficient around a horizontal heating element in gas-solid fluidized bed and concluded that the heat transfer rate is observed maximum at the 0 degree and minimum at 180 degree from the bottom of the chamber. They also carried out experiments in a laboratory gas-solid fluidized bed heat exchanger. Heat transfer coefficient between immersed heated tube and bubbling fluidized bed is found experimentally around a tube. An experiment is performed with three different particle diameter and ten different superficial gas velocities. The bed particles used were Geldart B silica sand particles of diameter 200µm, 350µm and 500µm. Fluidizing media used was atmospheric air. The experimental result shows that Heat transfer coefficient is increase with increase in the air velocity and it is found to be decreased by increased in the particle size for Geldart B group particles. G.K.Roy& K.J. R. Sarma(1970) concluded that the heat transfer in fluidized bed is by convection. Francesco Miccio, Andrea De Riccardis, Michele Miccio (2009) determined the heat transfer coefficient for bubbling fluidized bed. Araí A. BernárdezPécora and Maria Regina Parise, (2006) concluded that Heat transfer coefficient increases with the solid particle mass flow rate. Jelena N. Janevski, BranislavStojanović, (2004) concluded that thermal conductivity depends on the intensity of mixing and heat transfer rate is higher in axial direction than radial direction.

2. EXPERIMENTAL PROGRAMME

The two-dimensional fluidized-chamber (shown schematically in Fig. 1) is 150 mm in length, 120 mm width and 800 mm tall (internal dimensions), constructed of 1 mm thick galvanized sheets. This fluidizing air is regulated by butterfly valve before passing through a sintered-metal plate distributor. Metal distribute plate is fixed in between fluidizing chamber and lower rectangular funnel. Pressure drop across the distributor is sufficiently high that at most fluidizing conditions it exceeds the pressure drop over the rest of the bed.

Fluidized bed heat exchange chamber contains bed of sand particles which is of same dimension as that of fluidizing chamber; the height of sand bed is 120 mm with inserted cartage heater (thermal coils⁷) as well as systems of air supply, and heat supply from the dimmer stat⁸. The heating coil is located 100 mm above from the bottom of the fluidized bed. The heater has dimension of 15 mm diameter. The surface of the active side of the heater is inserted in the sand particles. Air enters from the blower¹ and is transferred through the pipes towards the nozzle⁶ connecting the distributor plate in the fluidized bed and the blower pipeline. Quartz sand³ with diameters in the range of 300-450µm, 425-650µm and 600-850µm was employed in fluidized bed. The power of the heat exchanger can be varied using a dimmer stat.

Air from the blower is supplied from the atmosphere and ambient temperature and pressure. The air from the blower is connected through a butterfly valve where the velocity of the air coming can be controlled.

International Journal of Engineering Research and General Science Volume 2, Issue 2, Feb-Mar 2014 ISSN 2091-2730



Figure 2: General Experiment setup

(1.Blower, 2.Fluidised bed chamber, 3.Be particles, 4.Support, 5.Valve (butterfly valve),

6. Distributor plate setup, 7. Thermal coils (with fins and without fins))

Readings are taken by taking one sand particle at different velocities. All the readings are taken at a steady state. Likewise all the readings are taken for different sand particle, with varied velocity of air.

2.1 INSTRUMENTATION

In the setup, different 4 number of k type thermo couples are attached to the chamber in contact with sand bed, for getting different temperature reading from different places of fluidized bed. 2 more thermo couples are attached on the upper and lower surface of cartage heater for giving the temperature reading. A Voltmeter and Ammeter is used to vary the voltage and current. A blower of the capacity $1.5 \text{ m}^3/\text{min}$. is used to supply compressed air to the fluidizing column through diffuser and distributor plate. A butterfly valve mounted over an inlet pipe allows regulating the rate of flow of air. A differential manometer is connected across an orifice meter. Readings of the manometer is calibrated to get the velocity of the inlet air. Another differential manometer is connected to the fluidizing medium to find the pressure drop across the column.

3. RESULTS





www.ijergs.org





Figure 4: Distribution of heat transfer coefficient in different velocities for Sand particles size 425-650µm.





4. CONCLUSIONS

- [1] Silica sand is having good fluidizing properties.
- [2] The overall heat transfer coefficient h increases with increase in velocity and as the particle size increase, the heat transfer coefficient decreased. This is proved in fig.3, 4 and 5.
- [3] Heat transfer coefficient between heated tube and silica sand varies between 80 to 250 W/m²K.

ACKNOWLEDGEMENT

[4] This work is carried out at the Mechanical Department, Manoharbhai Patel institute of Engineering and technology, Shahapur, Bhandara, Maharashtra.

REFERENCES:

[1] Prof Antonia D'Alessi "Investigations on Heat Transfer Between a Bubbling Fluidized Bed and Immersed Tubes for Heat Recovery and Power Generation" from *Istituto di RicerchesullaCombustione - C.N.R., Napoli - ITALY* (2009)

International Journal of Engineering Research and General Science Volume 2, Issue 2, Feb-Mar 2014 ISSN 2091-2730

- [2] P. Makkonen, M. Mäkipää "Materials for Fluidized Bed Heat Exchangers" VTT Processes, Biologinkuja 5, P.O. Box 1601, FIN-02044, VTT, Finland(2003)
- [3] Ming-Yen Wey, Chiou-Liang Lin and Shr-Da You "FLUIDIZED BEHAVIOR AND HEAT TRANSFER IN A BUBBLING FLUIDIZED BED INCINERATOR" in National Chung Hsing University Taichung 402, Taiwan (2007)
- [4] David Roberto Escudero "Bed height and material density effects on fluidized bed hydrodynamics" from *Iowa State* University (2010)
- [5] W. Kasieczka, J. Jarosinski "Application of Fluidized Bed for Intensification of Heat Transfer in Heat Exchangers" fromTechnical University of Lodz, Poland(2005)
- [6] Hamid Reza Goshayeshi , John Missenden "Heat Transfer Modeling and Thermal Analysis for a Fluidized Bed" from *Journal* of Technical Engineering Islamic Azad University-Mashhad Branch Iran(2007)
- [7] G. K. ROY & K. J. R. SARMA "Fluidized bed heat transfer" from Department of Chemical Engineering, Regional Engineering College, Rourkela-8.of February 1970
- [8] Araí A. BernárdezPécora and Maria Regina Parise "Heat Transfer Coefficient in a Shallow Fluidized Bed Heat Exchanger with a Continuous Flow of Solid Particles" from The State University of Campinas Faculty of Mechanical Engineering 13083-970 Campinas, SP. Brazil of July-September 2006, Vol. XXVIII, No. 3 /253
- [9] P. Makkonen, M. Mäkipää "Materials for Fluidized Bed Heat Exchangers"VTT Processes, Biologinkuja 5, P.O. Box 1601, FIN-02044, VTT, Finland(2002)
- [10] SomchartSoponronnarit "FLUIDISED BED GRAIN DRYING" School of Energy and Materials King Mongkut's University of Technology ThonburiSuksawat 48 Road, Bangkok 10140, Thailand(2003)
- [11] Maan S. Al- Dabbagh "Experimental Study of heat Transfer between the Shallow Fluidized bed and a Tube Bundle Immersed in it" Department of Mechanical Engineer University Of Mosul - IRAQ (2006)
- [12] C. Stuart Daw "Characterizing the Hydrodynamics of Bubbling Fluidized Beds with Multivariate Pressure Measurements" Oak Ridge National Laboratory Oak Ridge TN 37831-8088(2000)
- [13] L.M. Armstrong, S. Gu*, K.H. Luo "Study of wall-to-bed heat transfer in a bubbling fluidised bed using the kinetic theory of granular flow" Energy Technology Research Group, School of Engineering Sciences, University of Southampton, Southampton, SO17 1BJ, United Kingdom(2010)
- [14] K.S.K. RaoPatnaik, Member, IACSIT and K. Sriharsha "Fluidization Principles for Three-Phase Fluidized Bed Bio-Reactor" of International Journal of Chemical Engineering and Applications, Vol. 1, No. 3, October 2010 ISSN: 2010-0221
- [15] SankaranSundaresan "INSTABILITIES IN FLUIDIZED BEDS" from Department of Chemical Engineering, Princeton University, Princeton, New Jersey 08544(2003)
- [16] Jonas A. England "Numerical Modeling and Prediction of Bubbling Fluidized Beds" from Francine Battaglia, Chair Thomas E. Diller RangaPitchumani April 27, 2011
- [17] C. Srinivasakannan and N. Balasubramaniam "Particle Growth in Fluidised Bed Granulation" from School of Chemical Engineering, Engineering Campus, UniversitySains Malaysia, 14300 NibongTebal, Pulau Penang, Malaysia(2003)
- [18] F.A.Zenz "THE FLUID MECHANICS OF BUBBLING BEDS" Manhattan College, Riverdale, New York 10471(1986)
- [19] PAUL DURU, M NICOLAS, JOHN HINCHAND E LI SABETH GUAZZELLI "Constitutive laws in liquid-fluidized beds" from IUSTI, CNRS-UMR 6595, Technop ole Chateau-Gombert, 13453 Marseille cedex 13, France AMTP, University of Cambridge, Silver Street, Cambridge CB3 9EW, UK(2002)
- [20] AfsinGungor "NUMERICAL COMPUTATION OF HYDRODYNAMIC BEHAVIOR OF BIOMASS PARTICLES IN CIRCULATING FLUIDIZED BEDS" from Nigde University of Refereed Proceedings The 13th International Conference on Fluidization - New Paradigm in Fluidization Engineering (2010)
- [21] Anusaya M. Salwe (2013)"Local heat transfer coefficient around a horizontal heating element in gas-solid fluidized bed" from University of pune, International Journal of Application or Innovation in Engineering & Management.